



MONOWATT
NATURAL ENERGY

MODULE SERIES
MW 255 - 270 - SB - 96C SHADOWBLACK

MODULE TYPES

MW 255 SB, MW 260 SB, MW 265 SB, MW 270 SB



SWISSWATT

Schlätliweg 1

9052 Niederteufen, Switzerland

fon: +41 (0)71 511 56 10

fax: +41 (0)71 511 56 19

email: info@swiss-watt.com

web: www.swiss-watt.com

The electrical parameters are typical values from historical production data. Measuring tolerance $\pm 3\%$.

Technical changes in the course of product development, mistakes and errors reserved. Data sheet MW255 - 270 96c Shadow Black V02:13

PRODUCT FEATURES

MONOWATT Modules SHADOW BLACK with 96 cells offer 4 performance classes designed for roof - or ground mounting. The modules are best suitable for small, medium and large scale solar systems for on- or off-grid operations. For All who like it BLACK: With black powdered frame and black backsheet. SWISSWATT technology, design and construction guarantee the highly efficient and reliable long term output of each and every module. Our automatic production and our latest flash tower technology guarantee a documented performance above industry standard.

- + 72 monokristalline solarcells
- + Industry leading power tolerance 0 - + 3 %
- + Unique frame design for insolation and weather exposure
- + Automatic clean-room production for sustainable returns
- + Frame mounting concept for long- and short side mounting
- + High transmission low iron tempered glass
- + Enhanced strength and impact resistance
- + Advanced EVA component encapsulation, multilayer backsheet technology

WARRANTIES & ASSURANCES

Industry leading guaranty on material and manufacturing: 10 years

Output assurance: up to 12 years: 90 %, up to 25 years: 80%

Please refer to our warranty conditions


QUALIFICATIONS & CERTIFICATES

Ongoing quality control and performance testing executed by independent testing laboratories grant the maximal benefit of your environmentally friendly energy production.

IEC 61215.2 / IEC 61730 / safety class II



TECHNICAL DATA MODULE SERIES MW 255 - 270 - SB - 96C



MECHANICAL DATA & MEASURES

Cable type, Diameter, Length	4 mm ² , TÜV certified, 900 mm
Connector type	Type III and Type IV compatible
Dimension (mm)	1580 x 1069 x 45
Weight	25
Drainage Holes in Frame	10
Glass, Type, Thickness	High Transmission, Low Iron, 3,2 mm Tempered Glass
Junction box	Ip 65
Bypass-Diodes	4

ABSOLUTE RATINGS

Dielectric Insulation Voltage (V)	3000 V
Operating Temperature (°C)	-40 ~ +85
Storage Temperature (°C)	-40 ~ +85
Mechanical Load	5400 Pa up to 10000 Pa extrem

MODULE SERIES MW 255 - 270 - SB - 96C

Max-System Voltage (VDC)	600V(UL) / 1000V(IEC)
Number, type and arrangement of cells	96, Mono-Crystalline Silicon (8 x 12)
Cell Size (mm)	125 x 125
Max. Series fuse (A)	15
Module variants	MONOWATT (255-280W), Indus, extrem



ELECTRICAL DATA AT STC / NOCT (47 ± 2°C)

Module type	MW255SB	MW260SB	MW265SB	MW270SB
Rated output P _{MPP} (W)	255 Wp	260 Wp	265 Wp	270 Wp
Max-Power Voltage V _m (V)	51,3 / 45,76 V	51,5 / 45,94 V	51,7 / 46,12 V	51,9 / 46,30 V
Max-Power Current I _{MPP} (A)	4,97 / 4,2 A	5,05 / 4,28 A	5,13 / 4,35 A	5,2 / 4,41 A
Open circuit Voltage V _{OC} (V)	61,3 / 55,97 V	61,5 / 56,15 V	61,8 / 56,42 V	62,1 / 56,7 V
Short circuit voltage I _{SC} (A)	5,4 / 4,59 A	5,49 / 4,67 A	5,53 / 4,7 A	5,59 / 4,75 A
Cell Efficiency (%)	17,80%	18,20%	18,60%	18,90%
Module efficiency %	15,10%	15,40%	15,70%	16,00%

CURRENT-VOLTAGE CURVE (I-V-CURVE)

I-V Curve

The current in relation to the voltage, illustrates the cell performance at different irradiances and temperatures. (AM1.5; 25°C)



THERMAL CHARACTERISTICS

Pm Temperature Coefficient (%/K)	-0,4454
Isc Temperature Coefficient (%/K)	0,0499
Voc Temperature Coefficient (%/K)	-0,3336